

| 500 KM INSPECTION | | CHECKED |
|---------------------|--------------------------------------------------|---------|
| Hitch | Check hitch bolts to 95Nm. | |
| | Lubricate with high temp bearing grease where | |
| | necessary. | |
| Handbrake | Inspect and adjust handbrake as needed. | |
| Brakes | Check brakes are operating as per normal behind | |
| | your tow vehicle and have bedded in properly. | |
| Wheel Nuts | Inspect condition and torque to 135Nm. | |
| Tyres | Inspect for abnormal wear and damage. | |
| General Observation | General inspection to ensure no loose fixings or | |
| | fittings. Advise Signature Campers of any | |
| | observations. | |
| DATE: | SERVICE PERSON: | |
| | | |
| | | |
| WORKSHOP STAMP: | | |
| | | |
| | | |
| | | |
| | | |
| | | |



| 6 MONTHS / 5000 KM SERVICE | | CHECKE |
|-------------------------------|------------------------------------------------------------------------------------------------------------------|--------|
| Hitch | Check hitch bolts to 95Nm. Lubricate coupling if necessary. | |
| Safety chains, Jockey wheel | Check safety chains, jockey wheel and stabiliser legs | |
| and Stabilisers | for safe operation. | |
| Handbrake | Inspect and adjust handbrake as needed. | |
| Brakes and Bearings | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly. | |
| Swing Arms | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm. | |
| Brakes | Inspect and adjust. Check lining thickness and drum wear. | |
| Wheel Bearings | Remove, clean and re-grease. Inspect for wear and replace if necessary. | |
| Wheel Nuts | Inspect condition and torque to 135Nm. | |
| Tyres and Rims | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate. | |
| Lights | Check all lights are functioning. | |
| Battery | Check terminals and voltage. | |
| Seals | Check seal condition and latch tension to 30-40% compression on automotive seal. | |
| General Observation and | General inspection to ensure no loose fixings or | |
| Lubrication | fittings. Grease all accessible grease points. Advise Signature Campers of any observations. | |
| DATE: | SERVICE PERSON: | |
| WORKSHOP STAMP: | | |



| 18 MONTHS / 15000 KM SERVICE | | CHECKED |
|---------------------------------|------------------------------------------------------------------------------------------------------------------|---------|
| Hitch | Check hitch bolts to 95Nm. Lubricate coupling if necessary. | |
| Safety chains, Jockey wheel | Check safety chains, jockey wheel and stabiliser legs | |
| and Stabilisers | for safe operation. | |
| Handbrake | Inspect and adjust handbrake as needed. | |
| Brakes and Bearings | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly. | |
| Swing Arms | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm. | |
| Brakes | Inspect and adjust. Check lining thickness and drum wear. | |
| Wheel Bearings | Remove, clean and re-grease. Inspect for wear and replace if necessary. | |
| Wheel Nuts | Inspect condition and torque to 135Nm. | |
| Tyres and Rims | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate. | |
| Lights | Check all lights are functioning. | |
| Battery | Check terminals and voltage. | |
| Seals | Check seal condition and latch tension to 30-40% compression on automotive seal. | |
| General Observation and | General inspection to ensure no loose fixings or | |
| Lubrication | fittings. Grease all accessible grease points. Advise Signature Campers of any observations. | |
| DATE: | SERVICE PERSON: | |
| WORKSHOP STAMP: | | |



| 30 MONTHS / 25000 KM SERVICE | | CHECKE |
|---------------------------------|------------------------------------------------------------------------------------------------------------------|--------|
| Hitch | Check hitch bolts to 95Nm. Lubricate coupling if necessary. | |
| Safety chains, Jockey wheel | Check safety chains, jockey wheel and stabiliser legs | |
| and Stabilisers | for safe operation. | |
| Handbrake | Inspect and adjust handbrake as needed. | |
| Brakes and Bearings | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly. | |
| Swing Arms | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm. | |
| Brakes | Inspect and adjust. Check lining thickness and drum wear. | |
| Wheel Bearings | Remove, clean and re-grease. Inspect for wear and replace if necessary. | |
| Wheel Nuts | Inspect condition and torque to 135Nm. | |
| Tyres and Rims | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate. | |
| Lights | Check all lights are functioning. | |
| Battery | Check terminals and voltage. | |
| Seals | Check seal condition and latch tension to 30-40% compression on automotive seal. | |
| General Observation and | General inspection to ensure no loose fixings or | |
| Lubrication | fittings. Grease all accessible grease points. Advise Signature Campers of any observations. | |
| DATE: | SERVICE PERSON: | |
| WORKSHOP STAMP: | | |



| 42 MONTHS / 35000 KM SERVICE | | CHECKED |
|---------------------------------|------------------------------------------------------------------------------------------------------------------|---------|
| Hitch | Check hitch bolts to 95Nm. Lubricate coupling if necessary. | |
| Safety chains, Jockey wheel | Check safety chains, jockey wheel and stabiliser legs | |
| and Stabilisers | for safe operation. | |
| Handbrake | Inspect and adjust handbrake as needed. | |
| Brakes and Bearings | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly. | |
| Swing Arms | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm. | |
| Brakes | Inspect and adjust. Check lining thickness and drum wear. | |
| Wheel Bearings | Remove, clean and re-grease. Inspect for wear and replace if necessary. | |
| Wheel Nuts | Inspect condition and torque to 135Nm. | |
| Tyres and Rims | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate. | |
| Lights | Check all lights are functioning. | |
| Battery | Check terminals and voltage. | |
| Seals | Check seal condition and latch tension to 30-40% compression on automotive seal. | |
| General Observation and | General inspection to ensure no loose fixings or | |
| Lubrication | fittings. Grease all accessible grease points. Advise | |
| | Signature Campers of any observations. | |
| DATE: | SERVICE PERSON: | |
| WORKSHOP STAMP: | | |



| 60 MONTHS / 45000 KM SERVICE | | CHECKE |
|---------------------------------|------------------------------------------------------------------------------------------------------------------|--------|
| Hitch | Check hitch bolts to 95Nm. Lubricate coupling if necessary. | |
| Safety chains, Jockey wheel | Check safety chains, jockey wheel and stabiliser legs | |
| and Stabilisers | for safe operation. | |
| Handbrake | Inspect and adjust handbrake as needed. | |
| Brakes and Bearings | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly. | |
| Swing Arms | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm. | |
| Brakes | Inspect and adjust. Check lining thickness and drum wear. | |
| Wheel Bearings | Remove, clean and re-grease. Inspect for wear and replace if necessary. | |
| Wheel Nuts | Inspect condition and torque to 135Nm. | |
| Tyres and Rims | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate. | |
| Lights | Check all lights are functioning. | |
| Battery | Check terminals and voltage. | |
| Seals | Check seal condition and latch tension to 30-40% compression on automotive seal. | |
| General Observation and | General inspection to ensure no loose fixings or | |
| Lubrication | fittings. Grease all accessible grease points. Advise Signature Campers of any observations. | |
| DATE: | SERVICE PERSON: | |
| WORKSHOP STAMP: | | |