



**Service and Maintenance Schedule – Iridium 13 & 13S**

| 500 KM INSPECTION   |                                                                                                          | CHECKED |
|---------------------|----------------------------------------------------------------------------------------------------------|---------|
| Hitch               | Check hitch bolts to 95Nm.<br>Lubricate with high temp bearing grease where necessary.                   |         |
| Handbrake           | Inspect and adjust handbrake as needed.                                                                  |         |
| Brakes              | Check brakes are operating as per normal behind your tow vehicle and have bedded in properly.            |         |
| Wheel Nuts          | Inspect condition and torque to 135Nm.                                                                   |         |
| Tyres               | Inspect for abnormal wear and damage.                                                                    |         |
| General Observation | General inspection to ensure no loose fixings or fittings. Advise Signature Campers of any observations. |         |
| DATE:               | SERVICE PERSON:                                                                                          |         |
| WORKSHOP STAMP:     |                                                                                                          |         |



**Service and Maintenance Schedule – Iridium 13 & 13S**

| 6 MONTHS /<br>5000 KM SERVICE               |                                                                                                                                               | CHECKED |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Hitch                                       | Check hitch bolts to 95Nm. Lubricate coupling if necessary.                                                                                   |         |
| Safety chains, Jockey wheel and Stabilisers | Check safety chains, jockey wheel and stabiliser legs for safe operation.                                                                     |         |
| Handbrake                                   | Inspect and adjust handbrake as needed.                                                                                                       |         |
| Brakes and Bearings                         | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly.                              |         |
| Swing Arms                                  | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm.                                                                     |         |
| Brakes                                      | Inspect and adjust. Check lining thickness and drum wear.                                                                                     |         |
| Wheel Bearings                              | Remove, clean and re-grease. Inspect for wear and replace if necessary.                                                                       |         |
| Wheel Nuts                                  | Inspect condition and torque to 135Nm.                                                                                                        |         |
| Tyres and Rims                              | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate.                                                |         |
| Lights                                      | Check all lights are functioning.                                                                                                             |         |
| Battery                                     | Check terminals and voltage.                                                                                                                  |         |
| Seals                                       | Check seal condition and latch tension to 30-40% compression on automotive seal.                                                              |         |
| General Observation and Lubrication         | General inspection to ensure no loose fixings or fittings. Grease all accessible grease points. Advise Signature Campers of any observations. |         |
| DATE:                                       | SERVICE PERSON:                                                                                                                               |         |
| WORKSHOP STAMP:                             |                                                                                                                                               |         |



**Service and Maintenance Schedule – Iridium 13 & 13S**

| <b>18 MONTHS /<br/>15000 KM SERVICE</b>     |                                                                                                                                               | <b>CHECKED</b> |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Hitch                                       | Check hitch bolts to 95Nm. Lubricate coupling if necessary.                                                                                   |                |
| Safety chains, Jockey wheel and Stabilisers | Check safety chains, jockey wheel and stabiliser legs for safe operation.                                                                     |                |
| Handbrake                                   | Inspect and adjust handbrake as needed.                                                                                                       |                |
| Brakes and Bearings                         | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly.                              |                |
| Swing Arms                                  | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm.                                                                     |                |
| Brakes                                      | Inspect and adjust. Check lining thickness and drum wear.                                                                                     |                |
| Wheel Bearings                              | Remove, clean and re-grease. Inspect for wear and replace if necessary.                                                                       |                |
| Wheel Nuts                                  | Inspect condition and torque to 135Nm.                                                                                                        |                |
| Tyres and Rims                              | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate.                                                |                |
| Lights                                      | Check all lights are functioning.                                                                                                             |                |
| Battery                                     | Check terminals and voltage.                                                                                                                  |                |
| Seals                                       | Check seal condition and latch tension to 30-40% compression on automotive seal.                                                              |                |
| General Observation and Lubrication         | General inspection to ensure no loose fixings or fittings. Grease all accessible grease points. Advise Signature Campers of any observations. |                |
| DATE:                                       | SERVICE PERSON:                                                                                                                               |                |
| WORKSHOP STAMP:                             |                                                                                                                                               |                |



**Service and Maintenance Schedule – Iridium 13 & 13S**

| <b>30 MONTHS /<br/>25000 KM SERVICE</b>     |                                                                                                                                               | <b>CHECKED</b> |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Hitch                                       | Check hitch bolts to 95Nm. Lubricate coupling if necessary.                                                                                   |                |
| Safety chains, Jockey wheel and Stabilisers | Check safety chains, jockey wheel and stabiliser legs for safe operation.                                                                     |                |
| Handbrake                                   | Inspect and adjust handbrake as needed.                                                                                                       |                |
| Brakes and Bearings                         | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly.                              |                |
| Swing Arms                                  | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm.                                                                     |                |
| Brakes                                      | Inspect and adjust. Check lining thickness and drum wear.                                                                                     |                |
| Wheel Bearings                              | Remove, clean and re-grease. Inspect for wear and replace if necessary.                                                                       |                |
| Wheel Nuts                                  | Inspect condition and torque to 135Nm.                                                                                                        |                |
| Tyres and Rims                              | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate.                                                |                |
| Lights                                      | Check all lights are functioning.                                                                                                             |                |
| Battery                                     | Check terminals and voltage.                                                                                                                  |                |
| Seals                                       | Check seal condition and latch tension to 30-40% compression on automotive seal.                                                              |                |
| General Observation and Lubrication         | General inspection to ensure no loose fixings or fittings. Grease all accessible grease points. Advise Signature Campers of any observations. |                |
| DATE:                                       | SERVICE PERSON:                                                                                                                               |                |
| WORKSHOP STAMP:                             |                                                                                                                                               |                |



**Service and Maintenance Schedule – Iridium 13 & 13S**

| <b>42 MONTHS /<br/>35000 KM SERVICE</b>     |                                                                                                                                               | <b>CHECKED</b> |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Hitch                                       | Check hitch bolts to 95Nm. Lubricate coupling if necessary.                                                                                   |                |
| Safety chains, Jockey wheel and Stabilisers | Check safety chains, jockey wheel and stabiliser legs for safe operation.                                                                     |                |
| Handbrake                                   | Inspect and adjust handbrake as needed.                                                                                                       |                |
| Brakes and Bearings                         | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly.                              |                |
| Swing Arms                                  | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm.                                                                     |                |
| Brakes                                      | Inspect and adjust. Check lining thickness and drum wear.                                                                                     |                |
| Wheel Bearings                              | Remove, clean and re-grease. Inspect for wear and replace if necessary.                                                                       |                |
| Wheel Nuts                                  | Inspect condition and torque to 135Nm.                                                                                                        |                |
| Tyres and Rims                              | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate.                                                |                |
| Lights                                      | Check all lights are functioning.                                                                                                             |                |
| Battery                                     | Check terminals and voltage.                                                                                                                  |                |
| Seals                                       | Check seal condition and latch tension to 30-40% compression on automotive seal.                                                              |                |
| General Observation and Lubrication         | General inspection to ensure no loose fixings or fittings. Grease all accessible grease points. Advise Signature Campers of any observations. |                |
| DATE:                                       | SERVICE PERSON:                                                                                                                               |                |
| WORKSHOP STAMP:                             |                                                                                                                                               |                |



**Service and Maintenance Schedule – Iridium 13 & 13S**

| <b>60 MONTHS /<br/>45000 KM SERVICE</b>     |                                                                                                                                               | <b>CHECKED</b> |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Hitch                                       | Check hitch bolts to 95Nm. Lubricate coupling if necessary.                                                                                   |                |
| Safety chains, Jockey wheel and Stabilisers | Check safety chains, jockey wheel and stabiliser legs for safe operation.                                                                     |                |
| Handbrake                                   | Inspect and adjust handbrake as needed.                                                                                                       |                |
| Brakes and Bearings                         | Inspect and adjust brakes as they need to bed in. Check bearings are greased and castle nut tensioned correctly.                              |                |
| Swing Arms                                  | Lubricate and check bushes for excessive movement. Torque bolts to 135Nm.                                                                     |                |
| Brakes                                      | Inspect and adjust. Check lining thickness and drum wear.                                                                                     |                |
| Wheel Bearings                              | Remove, clean and re-grease. Inspect for wear and replace if necessary.                                                                       |                |
| Wheel Nuts                                  | Inspect condition and torque to 135Nm.                                                                                                        |                |
| Tyres and Rims                              | Inspect for abnormal wear and damage. Set to correct PSI if necessary. Check Compliance plate.                                                |                |
| Lights                                      | Check all lights are functioning.                                                                                                             |                |
| Battery                                     | Check terminals and voltage.                                                                                                                  |                |
| Seals                                       | Check seal condition and latch tension to 30-40% compression on automotive seal.                                                              |                |
| General Observation and Lubrication         | General inspection to ensure no loose fixings or fittings. Grease all accessible grease points. Advise Signature Campers of any observations. |                |
| DATE:                                       | SERVICE PERSON:                                                                                                                               |                |
| WORKSHOP STAMP:                             |                                                                                                                                               |                |